



Amarr® SuperFlex

Flexible Impact Section



Amarr SuperFlex impact resistant sections are the answer to lower door section damage common in today's busy warehouses.

Construction

- High-performance Thermoplastic Polyolefin (TPO) interior and exterior polymer skin
- Flexible fiberglass tube frame with steel corner brackets
- Insulated 1-3/4" thick section with an 8.5 R-value

Features

- Flexes in and out an average of 8"-10"
- Suitable for environmental temperatures from 20°F to 131°F (-7°C to 54°C)
- Retrofits to most 1-1/2" - 2" thick sectional doors
- Provides an exceptional thermal seal

Benefits

- Reduced lower door section damage
- Reduced maintenance costs
- Excellent UV resistance
- Outstanding chemical resistance
- Seals against tongue & groove or shiplap door sections

Hardware

- Easy installation
- Standard bottom brackets, rollers and rope included
- Standard heavy-duty, easy-grip lift handle included
- Hardware is NOT included for second section of two-section configuration
- Door lock is NOT included
- For proper flexibility, do not install center hinges on section

Size Availability

- Section heights: 18", 21" and 24"
- Section widths: 8'2", 9'2", 10'2" and 12'2" (custom widths available up to 12'2")

Door Availability

- One- or two-section configurations
- Amarr 2002/2012/2022, 2402/2412/2422 and 2502/2512/2522 ribbed panel doors
- Amarr 2742 and 2042 polyurethane insulated doors



Unique construction of the Amarr SuperFlex section allows it to flex; providing durability and reliable operations.



High impact polymer skin deflects minor blows from forks.



Amarr SuperFlex sections flex upon impact and return to normal operating position.



CSDdoors.com | 800-315-1680

1421 Stoneridge Drive
Middletown, PA 17057

ENTRE/MATIC

Entrematic
165 Carriage Court
Winston-Salem, NC 27105



Sectional door products from Entrematic may be the subject of one or more U.S. and/or foreign, issued and/or pending, design and/or utility patents. Entrematic and Amarr as words and logos are trademarks owned by Entrematic Group AB or companies within the Entrematic Group. Door specifications and technical data subject to change without notice.
©Entrematic Group AB 2017. All rights reserved. Printed in USA Form #6170217/8M/GVS